

# Ohýbací a štípací stroje



**PS**  
BETON MACHINE  
PSBETON.COM  
+420 606 681 030



Brněnská 543

664 42 Brno-Modřice

[www.psbeton.com](http://www.psbeton.com)

tel.: 00 420 606 681 030

[psbeton@psbeton.com](mailto:psbeton@psbeton.com)

## Ohybací stroje

PF30



PF32

PF36



PF42

PF52



Typ	HP	Práce	Počet tyčí	R50 kg/mm2	R65 kg/mm2	R85 kg/mm2	Rozměry	Hmotnost [kg]
PF30 1f	3	ohýbat	1	30	28	26	62x75x90	250
PF30 3f	2		2	24	22	20		
			3	18	16	18		
PF32 3f	3	ohýbat	1	32	30	26	65x85x90	280
			2	24	26	22		
			3	20	18	16		
PF36 3f	4	ohýbat	1	36	34	32	70x90x95	420
			2	26	24	22		
			3	24	20	18		
PF42 3f	5,5	ohýbat	1	42	38	36	70x90x95	460
			2	28	30	28		
			3	26	28	26		
PF52 3f	5,5	ohýbat	1	52	48	44	112x78x92	650
			2	36	36	34		
			3	30	28	26		

## Kombinovaný stroj

PF24/28

PF26/32

PF30/35



Typ	HP	Práce	Počet tyčí	R50 kg/mm2	R65 kg/mm2	R85 kg/mm2	Rozměry	Hmotnost [kg]
PFT24/28 1f.,3f	3	ohýbat	1	28	26	22	90x80x90	280
		ohýbat	2	20	18	16		
		ohýbat	3	16	14	12		
		štípat	1	24	24	22		
		štípat	2	16	18	16		
		štípat	3	12	16	14		
PFT26/32 3f	3	ohýbat	1	32	30	28	90x80x90	320
		ohýbat	2	24	22	20		
		ohýbat	3	20	20	18		
		štípat	1	26	24	22		
		štípat	2	18	18	16		
		štípat	3	16	16	14		
PFT30/35 3f	4	ohýbat	1	35	32	30	90x80x90	340
		ohýbat	2	26	24	22		
		ohýbat	3	20	20	18		
		štípat	1	30	28	26		
		štípat	2	20	24	22		
		štípat	3	16	18	16		

## Rovnáč stroj

### RT12



Tvarovatelné	Max. délka řezu	Rychlost oceli	Max. hmotnost oceli	Rozměry
6-8-10-12 mm	12.000 mm	35 m/min	2200 kg	200x100x160 cm

## Hydraulický řezací stroj

### S22HD

### S30HD

### S32HD

### S45HD

### S52HD



Typ	HP	Práce	Počet tyčí	R50 kg/mm2	R65 kg/mm2	R85 kg/mm2	Rozměry	Hmotnost [kg]
22HD monof.	2	štípat	1	20	18	16	89x51x85	75
22HD Trif.	2	štípat	1	20	18	16	89x51x85	75
30HD Monof.	3	štípat	1	30	30	26	89x51x85	180
32HD Trif.	4	štípat	1	32	32	30	105x53x91	215
45HD Trif.	5,5	štípat	1	45	42	38	133x68x87	380
52HD Trif.	7,5	štípat	1	52	46	44	133x68x87	450

## Řemenový stroj

### ST16



R50 KG/mm2	
Průměr	Počet tyčí
6	9
8	8
10	5
12	3
14	2
16	1

## Mechanický řezací stroj

S30

S32

S40

S45



Typ	HP	Práce	Počet tyčí	R50 kg/mm2	R65 kg/mm2	R85 kg/mm2	Rozměry	Hmotnost [kg]
S30 3f	3	štípat	1	30	26	24	90x50x45	180
S32 3f	4	štípat	1	32	28	26	90x50x45	190
S40 3f	5,5	štípat	1	40	32	30	100x68x60	300
S45 3f	7,5	štípat	1	45	34	34	100x68x60	330

## Čistící stroj

Limpia



Motor	Elektropumpa	Hodinová produkce	Pracovní rozměry
0,75 KW 1f/3f	0,11 KW	200 m2/h	V. 8–50 cm Š. 1–5 cm